

Maintenance of the PHD Pro carts

Before First Use & Weekly Sanitizing

After 7 days of non-use or more

We suggest you obtain an approved disinfectant (such as Steramine tablets). (Available at Hydrationcart.com) *A bottle of Steramine tablets has been included in your initial order

Follow instruction of sterilizer you are using (make sure it is food safe) add recommend number of tablets for gallon size of tank, completely fill to overflowing with potable water

- 1- Lock open all trigger guns and remove both hoses from left side of the Pump power pack. Let lines and tank drain.
- 2- Refill the tank again with potable water. completely full to overflowing with potable water. Add appropriate sterilizer for sterilizer instructions.
- 3- turn the pump on and run sterilized water thru all lines.
- 4- Repeat step one and after all lines and tank are drained, refill with water, you are ready, the unit is now ready to put into service.

Winterization of the Pure Pumper

When in sub-freezing temperatures (32°F and below) the hydration cart must be stored and kept in a climate-controlled area. Failure to do so can result in hoses, pump or nozzle failure. It is important to follow proper draining instructions even in climate-controlled area. You must winterize the unit (s) to avoid damage. This can be accomplished by draining the tank & hoses.

- 1- There are simply two fittings that can be unscrewed to drain the entire system. Simply remove both hoses from the pump pack and open all drink nozzles, this will completely drain they tank and system.
- 2- After draining the tan and lines turn the pump on for about 5 seconds to empty the pump of liquid,(DO NOT RUN PUMP DRY).



- 3- Place the batteries on the chargers. The chargers are smart chargers which can keep the batteries from discharging during the winter months.
- 4- Your unit is safe for winter.

Getting the Pure Pumper ready for Spring

- 1-Fill unit and check for operation and leaks. If you find an issue, please contact us for replacement parts or assistance. (Parts are Available at Hydrationcart.com)
- 2- Replace the Water Filter with new Water filter then Follow sanitizing steps 1 thru 5 stated above before putting unit in service. (Parts are Available at Hydrationcart.com)

If you have any further questions, please contact:

info@mzrallyworks.com
(785) 843-6086 ext 109

MZ Rally Works.com
Makers of Hydration Cart™ and Island Clean™ · Patents Pending